

The Durable Solution.

The perfect complement to our excellent stencil machines, Marsh oilboard provides you with powerful, long-lasting options for creating your own stencils. Our comprehensive selection of exceptionally high quality oil-treated paper board is cured in a plant that is solely dedicated to the production of superior grade oilboard. This curing process, which includes a treatment with a special blend of double-boiled linseed oils, helps resist ink bleed-through. After treatment with the oil, the board is cut with the grain in order to further strengthen its rigidity, resulting in clean, sharp marks with your stenciling system, including the stencil machine, ink, applicator, and oilboard.



Natural or Canary
Premium Grade Oilboard

Features:

- Specifically formulated to resist ink bleed-through
- Fine grade oilboard will not tear or pull when cut – saves time and money
- The largest selection of standard sizes available for all types of stencil machines
- Available in .015", .011" and .007" thickness in natural colored board
- Canary oilboard is premium grade – finer fibers produce extremely clear-cut characters
- Chart represents most common sizes – .015" thickness
- Recommended for 1", ¾" and ½" machines, including Marsh R, R-5, S, H and Super Size stencil machines
- All of the sizes indicated in chart are also available in natural .011" and .007" thickness
- Item codes for .011" are prefaced with OB11. Item Codes for .007" are prefaced with OB7
- Lightweight .011" or .007" thickness – must use with 1/4" machines (Marsh Model Q) and Stencil Express stencil machines
- Canary is only available in .015"
- Other standard and special cut sizes and rolls available. Please call for pricing and availability

Item–Natural	Item–Canary	Size	Carton Weight	Sheets (Appx.)
OB15-3X36-50	OBC15-3X36-50	3" x 36" (76 mm x 914 mm)	50 lb (23 kg)	833
OB15-4X16-50	OBC15-4X16-50	4" x 16" (102 mm x 406 mm)	50 lb (23 kg)	1432
OB15-4X20-50	OBC15-4X20-50	4" x 20" (102 mm x 508 mm)	50 lb (23 kg)	1143
OB15-4X36-50	OBC15-4X36-50	4" x 36" (102 mm x 914 mm)	50 lb (23 kg)	625
OB15-5X16-50	OBC15-5X16-50	5" x 16" (127 mm x 406 mm)	50 lb (23 kg)	1145
OB15-5X20-50	OBC15-5X20-50	5" x 20" (127 mm x 508 mm)	50 lb (23 kg)	914
OB15-5X24-50	OBC15-5X24-50	5" x 24" (127 mm x 610 mm)	50 lb (23 kg)	745
OB15-6X12-50	OBC15-6X12-50	6" x 12" (152 mm x 305 mm)	50 lb (23 kg)	1267
OB15-6X16-50	OBC15-6X16-50	6" x 16" (152 mm x 406 mm)	50 lb (23 kg)	954
OB15-6X20-50	OBC15-6X20-50	6" x 20" (152mm x 508 mm)	50 lb (23 kg)	762
OB15-6X24-50	OBC15-6X24-50	6" x 24" (152 mm x 610 mm)	50 lb (23 kg)	633
OB15-6X36-50	OBC15-6X36-50	6" x 36" (152 mm x 914 mm)	50 lb (23 kg)	417
OB15-6.5X20-50	OBC15-6.5X20-50	6.5" x 20" (165 mm x 508 mm)	50 lb (23 kg)	703
OB15-6.5X24-50	OBC15-6.5X24-50	6.5" x 24" (165 mm x 610 mm)	50 lb (23 kg)	585
OB15-6.5X32-50	OBC15-6.5X32-50	6.5" x 32" (165 mm x 813 mm)	50 lb (23 kg)	475
OB15-6.5X36-50	OBC15-6.5X36-50	6.5" x 36" (165 mm x 914 mm)	50 lb (23 kg)	425
OB15-7X20-50	OBC15-7X20-50	7" x 20" (178 mm x 508 mm)	50 lb (23 kg)	653
OB15-7X24-50	OBC15-7X24-50	7" x 24" (178 mm x 610 mm)	50 lb (23 kg)	549
OB15-7X36-50	OBC15-7X36-50	7" x 36" (178 mm x 914 mm)	50 lb (23 kg)	400
OB15-8X24-50	OBC15-8X24-50	8" X 24" (203 mm x 610 mm)	50 lb (23 kg)	480
OB15-8X36-50	OBC15-8X36-50	8" X 36" (203 mm x 914 mm)	50 lb (23 kg)	312
OB15-10X32-50	OBC15-10X32-50	10" X 32" (254 mm x 813 mm)	50 lb (23 kg)	300
OB15-11X24-50	OBC15-11X24-50	11" x 24" (279 mm x 610 mm)	50 lb (23 kg)	345
OB15-11X36-50	OBC15-11X36-50	11" x 36" (279 mm x 914 mm)	50 lb (23 kg)	230
OB15-12X24-50	OBC15-12X24-50	12" x 24" (305 mm x 610 mm)	50 lb (23 kg)	350
OB15-12X36-50	OBC15-12X36-50	12" x 36" (305 mm x 914 mm)	50 lb (23 kg)	208
OB15-20X24-50	OBC15-20X24-50	20" X 24" (508 mm x 610 mm)	50 lb (23 kg)	186
OB15-20X32-50	OBC15-20X32-50	20" X 32" (508 mm x 813 mm)	50 lb (23 kg)	139
OB15-24X36-50	OBC15-24X36-50	24" x 36" (610 mm x 914 mm)	50 lb (23 kg)	104